

**COOLING & HEATING HIRE SPECIALIST** 

# 250kW BOILER

## **CONTAINERISED**



Specification Overview		
Output Duty	250 kW 853,000 BTU	
Power Supply	240v 1ph N+E 50Hz	
Running Current	15 Amps	
Plug Type	32A 3 Pin BS4343	
Noise Levels	45 dBA @ 10 mtrs	
Fuel Type	Diesel Oil or Natural Gas	
Fuel Consumption	29 ltrs/hr (Oil)	
Water Connections	3" Storz	
Weight	2000 kg	
Dimensions (WxDxH)	2,400 x 3,000 x 2,400mm	



#### Our extensive and modern range of hire equipment includes:

Air Cooled Chillers from 5kW to 750kW. As Well as a Heat Pump Range from 10kW up to 200kW Single Units. Container & Packaged Boilers with Integral Pumps and Heat Exchangers Ranging from 100kW to 2mW. Portable Air Conditioning Units. Including: Exhaust Tube Units, Split Type Air Conditioners & Evaporative Coolers. Electric, Gas & Diesel Powered Heaters. Including: Fan Heaters, Infrared, Indirect Fired and Direct Fired Units.

## 250kW BOILER

### **CONTAINERISED**

	General	Heating	DHW
Nominal Output		100 - 250 kW	100 - 250kW
Temperature Range		25/90°C	25/60°C
Power Supply	240v 1ph N+E 50Hz		
Running Current	15 Amps		
Plug Type	32A 3 Pin BS4343		
Maximum Working Pressure		10 Bar	10 Bar
Safety Valves		3/10 Bar	10 Bar
Heat Exchanger		Yes	Yes
BMS Outputs	Yes		
Time Clock	Yes		
Frost Protection	Yes		
Design Flow			Max 6,630 ltrs/ hr @ 45°C
Pump Capacity		11,000 ltrs/hr @ 1 Bar	
Variable Temperature Control		Yes	Yes
Height of Flue Above Ground Level	3,500mm		
Expansion Vessel		300 ltrs	No
DHW Circulation System			Yes
Flexible Hose Connections	Storz Twist Lock		
Water Connections	Flow / Return / Cold Feed	3" Storz	2" Storz
Recirculation Connection			1" Storz
Fuel Type	Diesel Oil or Natural Gas		
Fuel Connections	External Oil Tank or 1¼" Gas Train		
Fuel Consumption	29 ltrs/hr (Oil)		
Noise Level	45 dBA @ 10 mtrs		
Handling Options	Fork Pockets 4 Point Lifting Eyes		
Weight	2000 kg		
Dimensions (WxDxH)	2,400 x 3,000 x 2,400mm		









